



PATENTED PRODUCT Brochure

FOCUS ON OUTDOOR LED LIGHTING SINCE 2011
RELIABLE QUALITY, REASONABLE PRICE

DOB Ultrathin LED Underground Light

AC110-265V/IP67/Ra>80/1.5KV/80LM/W


Most Competitive Price (30% Off)



▲ JD-DM80D

▲ JD-DM100D



▲ JD-DM140D



▲ Back Side

DOB Ultrathin LED Underground Light

Model	Size	Open Size	Watt	Lumens	Voltage	CCT	Specification	N.W (KGS)
JD-DM80D	φ80*H45mm	φ75*45mm	3W	230-245LM	AC110-265V	WW3000K /CW6000K	[Material]:201 Stainless steel+Die-casting Aluminum+PC [Beam Angle]:30° [LED Chip]:SMD3030 [Wire]:0.3M 3*0.5mm ² PVC CRI>80 SDCM: 3.6 PF>0.5 Surf:1.5KV IP67(Full of glue) Two years warranty	195G
JD-DM100D	φ100*H55mm	φ95*55mm	5W	400-420LM	AC110-265V	WW3000K /CW6000K		300G
JD-DM140D	φ140*H55mm	φ120*55mm	12W	960-1060LM	AC110-265V	WW3000K /CW6000K		550G



COB LED Underground Light

30°-45°/IP67/Irradiation distance 3-10M/80-90lm/w

Private Patent No.:ZL201920047220.8



JD-DM100P / 7W


JD-DM150P / 10W

JD-DM200P / 20W

💡 GLOWING EFFECT



Model	Watt	Size(mm)	Open Size (mm)	Beam Angle	Total Lumens	Specification
JD-DM100P	7W	φ100*H80	φ90*H80mm	30°	600-630LM	LED Chip:COB Material:Stainless steel+Die-casting Aluminum+Acrylic Lens+PC+Toughened glass Voltage:AC85-265V or AC/DC12V CCT:3000K/6000K/4000K IP Grade:IP67 IK08 Wire:0.3M 3*0.75mm ² PVC Irradiation distance:3-10M
JD-DM150P	10W/15W	φ150*H90	φ140*H90mm	30°	800-850LM 1200-1300LM	
JD-DM200P	20W/30W	φ200*H90	φ190*H90mm	45°	1600-1700LM 2400-2550LM	



New COB Anti-glare LED Underground Light

5W/10W/15W/15°/24°/36°/IP67

Patent No.:ZL202230705547.7



JD-KD65W
5W
φ65*H80mm



JD-KD80W
10W
φ80*H125mm



JD-KD100W
15W
φ100*H140mm

Color:Black
Beam Angle:15°/24°/36°
LED Chip:COB
Material:Die-casting Aluminum+Anti-glare net+Acrylic Lens+PC
Wire:0.3M 3*0.75mm² PVC
Voltage:AC85-265V or AC/DC12V
CCT:3000K/4000K/6000K



New Plastic Fountain Pump and light

IP68/RGB/6W



Model No.	Plastic Fountain pump	Plastic Fountain Light	RF controller 72W	Parts
JD-FT125F	Watt:28W Voltage:AC220-240VV Size:18*98*100mm Pole:Height 19-32CM(Ajustable) Wire:6.9M with Two Pins Plug Water flow:1400L/H Lift distance:2M Curtain ceremony	Lamp Size:φ125*H23mm Middle Hole size:φ36mm Watt:6W CCT:RGB Voltage:DC12V LED Chips:SMD5050 6pcs Wire:5M 4*0.75PVC IP68	1.Watt:72W 2.Size:550*35*22mm 3.Control distance:4-6m 4.IP Grade:IP65 5.Description:with 16 kinds of static color,colorful gradient, colorful jump, colorful flashing and other dynamic functions,brightness adjustable,speed adjustable	1pcs 10W power supply DC12V IP65 1pcs M36 lock screw (18-25mm)



Ultrathin UFO LED Pool Light IP68 Private Model

DC12V/IP68/Fully filled with PU glue

Patent No.:202030781904.9



JD-YC120F
φ125*H25mm 4W



JD-YC180F
φ180*H28mm 8W

Lighting effect



Specification:
Material: White Plastic
Wire: 1M 2*0.75 PVC for single color
1M 4*0.5 PVC for RGB
Efficiency: 70-80LM/W
CCT: 3000K/6000K/RGB
LED Chip: 5W SMD5050 18PCS,
10W SMD5050 48PCS
Voltage: DC12V/IP68 CRI>80
Parts: Includes DN20 Connector
RGB need to buy remote controller

13 years of reliable manufacturer
for outdoor led lights

Hanging Ultrathin PC LED Pool Light

Patent Number: 202230140316.6



JD-YC125G



JD-YC125G-RGB




JD-YC210G




JD-YC210G-RGB

安装方法 INSTALLATION



Make your pool shine like a star with our Pool Light. It transforms your pool to look stunning with its subtle lighting effects.
Featuring next generation of SMD technology that emits out super bright light. With ripples in water, the light twinkles intriguing you every time.
Select a range of RGB colours with different modes using the remote control. Our product is rated waterproof IP68 which means it can stay submerged in water as long as you need. The lamp is also filled with resin to better its underwater performance.
This pool light screams durability! Made of PVC and PC cover material for long-lasting performance.

Model	JD-YC125G		JD-YC210G			
Size	φ125*H20mm		φ210*H20mm			
Watt	8W		18W		24W	
CCT	3000K/6000K	RGB	3000K/6000K	RGB	3000K/6000K	RGB
Acutal Lumen	750-850LM	/	1700-1800LM	/	2300-2400LM	/
LED Chip	SMD2835 100pcs	SMD3535 40pcs	SMD2835 432pcs	SMD5050 90pcs	SMD2835 432pcs	SMD5050 120pcs
Wire	2M 2*0.75 PVC	2M 4*0.5 PVC	2M 2*0.75 PVC	2M 4*0.5 PVC	2M 2*0.75 PVC	2M 4*0.5 PVC
Voltage	DC12V		DC12V		DC12V	
IP Grade	IP68		IP68		IP68	
Parts	Hanging Board+screws					
Controller	Need to buy one IR Infrared controller 72W IP65 for RGB					



Infrared Controller



The back of the product

New Surface mounted LED Pool Light IP68

Fully filled with PU Glue/PC/Easy to Install

Private Model Patent No.: 20203063546.2



JD-YC125MS
φ125*H28mm



JD-YC230MS
230*H36mm



Backside-small Backside-big




12key remote controller



JD-YC230MS-RGB

INSTALL DIAGRAM



Item No.	Size(mm)	Watt	CCT	LED Chip	Voltage	Specification
JD-YC120MS	φ125*H28mm	12W	3000K/6000K/Blue	SMD2835 140PCS	DC/AC12-24V	White PC Actual lumens:80-90LM/W Wire:2M 2*1.0 PVC IP68 RGB with 12key remote controller memory function Parts:Screws+Hole cap
			RGB	SMD5050 90pcs	AC12V	
JD-YC230MS	φ230*H36mm	18W/24W	3000K/6000K/Blue	SMD2835 432PCS	DC/AC12-24V	
		18W	RGB	SMD5050 90pcs	AC12V	
		24W	RGB	SMD5050 120pcs	AC12V	

13 years of reliable manufacturer for outdoor led lights

New PAR56 LED Pool Light IP68 18W/24W Private model

PC/Can be Replaced/Easy to Maintain/Fully Filled with PU Glue

Patent No.:ZL202230140316.6



JD-YCP56B
18W/24W

12key remote controller

Detailed Pictures



lighting source



backside of source




cover+screws



backside

Specification

Size:φ177*H28mm light source,Round PC Cover (φ233*H37mm)
18W/24W 3000K/6000K SMD2835 432PCS
AC/DC12-24V
18W RGB SMD5050 90pcs,24W 120pcs AC12V (with 12key remote controller,distance 20-30M,power off memory function)
2M 2*1.0 VDE Rubber
Parts:6pcs of clips and screws 2pcs of expansion screw kits.



New Ultra-thin Embedded 304# Stainless Steel Pool Lamp

IP68/DC12V/Fully filled with PU Glue/Private Model

lighting source can be replaced



JD-YC150Q



JD-YC245Q



lighting source can not be replaced



JD-YC120Q



JD-YC230Q



Model	Size (mm)	Watt	CCT	LED Chip	Remark	Specification
JD-YC150Q	φ150mm*H10 Open:120	8W	WW/CW	SMD2835/100PCS	lighting source can be replaced	[Voltage]:DC12V [Material]:304 stainless Steel+PC lampbody [Wire]:Single color 1M 2*0.75 PVC RGB 1M 4*0.5 PVC [IP Grade]:IP68 [Parts]:Screws [Remark]:RGB need to buy remote controller [Application]: widely used in swimming pool, spring,water view,artificial waterfall and other outdoor lightings.
			RGB	SMD3535/40PCS		
JD-YC245Q	φ245mm*H10 Open:230mm	24W	WW/CW	SMD2835/432PCS	lighting source can not be replaced	
			RGB	SMD5050/120PCS		
JD-YC120Q	φ120mm*H10 Open:90mm	8W	WW/CW	SMD2835/100PCS	lighting source can not be replaced	
			RGB	SMD3535/40PCS		
JD-YC230Q	φ230mm*H10 Open:180mm	24W	WW/CW	SMD2835/432PCS		
			RGB	SMD5050/120PCS		



13 years of reliable manufacturer for outdoor led lights




All in One IP65 Plastic Solar LED Garden Light 5W

JD-CD60TY-01




Solar LED Garden Light
Model: JD-CD60TY-01
CCT: 2700K/6000K/RGB
Watt: 5WCOB
Lampbody Size: φ60*H260mm
Solar Panel Power: 79.5*136*4mm
Solar Panel Power: 6V 1.5W
Battery capacity: 2000mAH
Charging time: 4-5H
Lighting time: 8-12H
Battery Type: Lithium battery/18650
Control mode: Light/time control
Lamp Material: ABS




Solar led garden light 2pcs in one IP65

JD-SC60-T2




Model No: JD-SC60-T2
CCT: 3000K/6500K/RGB
Watt: 2*5WCOB
Lamp body Size: $\phi 60 \times H260$ mm
Solar Panel size: 172*131mm
Solar Panel Power: 6V 3W
Battery capacity: 4000mAh
Charging time: 4-5H
Lighting time: 8-12H
Battery model: Lithium battery/18650
Control mode: Light control+key switch
Lamp body Material: ABS+fiber/black
Wire: 4 meter length, male and female waterproof connector, IP65




JD-SCD43-T3



JD-SCD43-T2



Material: die-casting aluminum
Color: Black
Control mode: automatic light control
Charge/Discharge: Charge time > 6H, Work time > 10H
Endurance: 2-3 rainy days
Wire: 4M 2*0.5PVC



Model No.	Lamp Size (mm)	Watt	CCT	Battery	Solar Panel
JD-SC43P-T2	$\phi 43 \times 240$ mm	2x5W COB	3000K/ 6500K	3.7V/4000mAh /18650	3W Poly-silicon 172*131mm
JD-SC43P-T3		3x5W COB			



JD-SC43-T3


JD-SC43-T4



JD-SC75C01-T3

JD-SC75C02-T3

Material: die-casting aluminum
Color: Black
Control mode: automatic light control
Charge/Discharge: Charge time > 6H, work time > 10H
Endurance: 2-3 rainy days
Wire: 5M 2*0.75PVC
Remark: Can be customized 2-4 pcs in one




Model No.	Lamp Size (mm)	Watt	CCT	Battery	Solar Panel
JD-SC43-T3	φ43*260mm	3x5W COB	3000K/6500K	3.7V 4000mAh /18650	6V/6W Polysilicon 270*180*17mm
JD-SC43-T4	φ43*260mm	4x5W COB	3000K/6500K	3.7V 6000mAh /18650	6V/10W Polysilicon 350*235*17mm
JD-SC75C01-T3	φ75*260mm	3x7W COB	3000K/6500K	3.7V 4000mAh /18650	6V/8W Polysilicon 350*235*17mm
JD-SC75C02-T3	φ75*260mm	3x7W COB	3000K/6500K	3.7V 4000mAh /18650	6V/8W Polysilicon 350*235*17mm

13 years of reliable manufacturer for outdoor led lights

Solar Stainless steel frame Tempered glass underground light



JD-SU150 3W φ150*90mm



JD-SU150-S φ150*90mm

Model No: JD-SU150

CCT: 3000K/6000K

LED Watt: 3W

Lamp body size: φ150*90mm

Solar panel size: 50*50mm

Solar panel power: 6V 0.6W

Battery capacity: 2000mAh

Lighting time: 8-12H

Charging time: 4-6H

Battery model: Lithium battery/18650

Control mode: light control / Intelligent switch

Lasting days: 2-3 rainy days

